



Rosslare Enterprises Ltd.

AC-B31 500 User PIN Controller



FEATURES

- 500 Users
- Internal keypad for programming, PIN only and PIN+PIN operation
- Internal buzzer
- Three modes of operation
 - Normal (PIN access)
 - Bypass
 - Secure (PIN + PIN access)
- Two bi-coloured status LEDs
- Built in case tamper detection
- Input for Request To Exit (REX)
- Bell chime, Siren and Strobe feature available with BL-D40
- Programmable Siren time
- Programmable lock release time
- Comes with mounting template for easy installation
- CE, UL and FCC approved

SPECIFICATIONS

Electrical Characteristics

Operating Voltage:
12 – 16V DC (Regulated)

Input Current @ 12V DC:

Standby: 20mA
Read: 75mA

Relay Output:
Electronic Relay, 4A

Inputs:
REX Normally open Dry Contact

Environmental Characteristics:

Operating Temperature Range:
-31° C to +63° C

Humidity:
0 – 95% (non-condensing)
Internal applications only

Dimensions:
92mm L x 92mm W x 24mm D



427 Maidstone Road, Wigmore, Kent ME8 OHY
Tel/Fax: 01634 374550
E-mail: info@readeroptions.com
www.readeroptions.com